

- Production OEM's
- Must have a minimum of 1000 units produced
- Up to 4 seats
- Engine Size - Max 1000cc
- Engine - must remain stock OEM
  - o No modifications allowed
- Forced Induction or Naturally Aspirated
  - o 25 mm restrictor plate fitted on all Turbo Charged units
- Speed - Max 85 mph
- Cooling - OEM
- Blow Off - OEM
- Boost - OEM
- Exhaust - OPEN
- Fuel Delivery - OEM
- Engine Electronic Management System - OEM
  - o No Flashing
- Transmission - OEM
- Differential - OEM
- Drive Line - OEM
- Chassis - OEM
  - o No shortening
  - o No lengthening
  - o Pivot Points - OEM
- Frame Material - Material may be added
  - o No material to be removed
- Seats - OPEN
- Body - OEM to include factory plastic
  - o Beds
  - o Taillights
  - o Minimal notching
- Interior Tub - to include Firewall
- Bumpers - Front and Rear 2" past tires
  - o Must be approved by BITD
- Roll Cage - Aftermarket required per BITD specs
  - o OEM must be approved by BITD
- Doors - may be operable
  - o Protection bars must meet BITD approval
- A-Arms - OEM Pivot Style and length
  - o May be replaced
- Ball Joints - OEM
- Uni Ball Joints - OEM
- Trailing Arms - OEM Pivot Style and length
  - o May be replaced
- Tie Rods - OEM mounting position
  - o May be replaced
- Radius Rods - OEM length and mounting position
  - o May be replaced
- Sway Bar - OEM length and mounting position
  - o May be replaced
- Suspension - OEM dimensions
- Shock Absorber - One coil over shock per wheel.
  - o May replace or modify
  - o Spring Rate Open
- Axles - OEM length and mounting position
  - o May be replaced
- Axel Hubs - OEM
- Uprights - OEM
- Steering Rack - OEM
- Steering Rack Power Unit - May be replaced
  - o Must bolt to OEM locations
- Brakes - OEM
- Fuel Capacity - Max 15 gallons
  - o OEM allowed
  - o Can replace OEM with Cell in tock location
  - o Or in bed with no removal of material to still allow for Bumpers and Roll Cages
  - o Additional aftermarket tank allowed with BITD approval
    - o Must be gravity fed
- Must be gravity fed
- Width - 80"
- Wheelbase - OEM
- Tire Size - 32 x 10.5