

- Production based modified class
- Must have a minimum of 250 units produced
- Open seating
- Must be All Wheel drive
- Engine Size - Max 1000cc
- Engine - OEM
- Engine Internals - OPEN
- Forced Induction or Naturally Aspirated
- Intercoolers - OPEN
- Blow Off Valve - OPEN
- Boost - OPEN
- Exhaust - OPEN
- Fuel Delivery - OPEN
- Engine Electronic Management system - OPEN
- Transmission - outer cases must remain OEM
 - o Internal modifications allowed
- Differentials - OPEN
- Drive Train - must remain OEM
 - o If delivered with a CVT belt, must use a CVT belt
 - o If delivered with an automatic transmission, must use automatic transmission
- Clutch - OPEN
- Chassis - May be complete tube replacement
 - o Pivots are OPEN
- Seating - Open
- Body - OPEN
- A-Arms - OPEN
- Trailing Arms - OPEN
- Suspension - OPEN
- Shock Absorber - OPEN
- Axles - OPEN
- Hubs - OPEN
- Uprights - OPEN
- Steering Racks - OPEN
- Steering Racks Power Unit - OPEN
- Brakes - OPEN
- Fuel Capacity - Cells are advised
 - o OEM Allowed in stock position
 - o No additional tanks allowed
- Max Width - 80"
- Max Wheelbase - 135"
- Max Tire - 35 x 10.5
- Max Rim - OPEN
- Must meet all BITD safety rules